

INT-TX Integrus

www.boschsecurity.com.cn



u	4	8	16	32
u	DCN			CCS 900
u				
u		/		

Integrus



-
-
- /
-
-
-
-
-
- /
- DCN
- DCN
- 19 (2U)
-

- 2 x 16 LCD
- /
-



-
- H 15
- LBB 3422/20
- 4 8 16 32
- 2 XLR

- 1
- 3.5 0.14

- 1 BNC HF
- 6 BNC HF 30
- 2 DCN *

* LBB 4416/xx



1 INT-TX Integrus

1 19

1

1



	100-240Vac	50-60Hz
	55W	
	29W	
	+3dBV (± 6dB)	+6dBV
	+15dBV (± 6dB)	+18dBV
	+6	+18dBV
	32	2
HF	1 Vpp	10mVpp
HF	75	
HF	1 Vpp	6VDC 75

x	x	
	92x440x410	3.6x17.3x16.1
19	88x483x410	3.5x19x16.1
	40	1.6
	370	14.6
	6.8	15.0

	19
	(PH10736)



INT-TX04 4

Integrus 4

INT-TX04

INT-TX08 8

Integrus 8

INT-TX08

INT-TX16 16

Integrus 16

INT-TX16

INT-TX32 32

Integrus 32

INT-TX32

INT-TX04-US 4

(US)

Integrus 4

INT-TX04-US

INT-TX08-US 8

(US)

Integrus 8

INT-TX08-US

INT-TX16-US 16

(US)

Integrus 16

INT-TX16-US

INT-TX32-US 32

(US)

Integrus 32

INT-TX32-US

LBB 3422/20

CCS 900

LBB3422/20

Integrus
LBB 3222/04 6



:	:
333	11 5
: 200335	506-509
: +86 21 22181111	:+852 2635 2815
: +86 21 22182388	:+852 2648 7986
www.boschsecurity.com.cn	www.boschsecurity.com.cn